

952.345 WHITE  
952.348 BLACK.

# GM-313 /313U

## INSTALLED BOUNDARY MICROPHONE

THE GM-313/~~313U~~ BOUNDARY MICROPHONE ARE DESIGNED FOR TABLE, CEILING OR PANEL MOUNIED APPLICATIONS.

THEY ARY SUITABLE FOR SOUND PICKUP IN TELECONFERENCING,RECORDING AND OTHER PURPOSES.

GM-313 IS WITH OMNIDIRECTIONAL PATTERN AND GM-313U IS UNIDIRECTIONAL PATTERN BOTH ARE BACK ELECTRETS CONDENSER ELEMENT.WITH A WIDE, FLAT RESPONSE TO ACHIEVE A GOOD SOUND REINFORCEMENT.

WHEN USING GM-313U,ITS UNIDIRECTTVITY CAN REDUCE AMBIENT NOISES AND ENHANCE A BETTER GAIN BEFORE FEEDBACK.

BOTH MODELS REQUIRE 9-52V DC PHANTOM POWER TO WORK, ALOW DISTORTION PRE-AMP BUILT INSIDE.BALANCED ~~XLR~~ OUTPUT.

XLR

### SPECIFICATIONS:

TYPE:.....CONDENSE~~R~~ MICROPHONE

POLAR PATTERN:.....GM-313 OMNIDIRECTIONAL

~~GM-313U UNIDIRECTIONAL~~

SENSITIVITY.....GM-313 -76dB±3dB

~~GM-313U -70dB±3DB~~

FREQUENCY RESPONSE:.....30 ~ 15KHz

MAXIMUM LNPUT SOUND LEVEL:.....120dB SPL 1KHz at 1% T.H.D.

PHANTOM POWER REQUIREMENTS.....9 ~ 52V

WEIGHT.....GM-313 100g

Dim. 30mm Ø x 71mm.

Cut out Ø. 20mm.

FREQUENCY RESPONSE  
PATTERN

POLAR