



● UT333 BT

### SPECIFICATIONS

	UT333	UT333BT
Temperature	-10°C~60°C 14°F~140°F	-10°C~60°C 14°F~140°F
Temperature accuracy	±1.0°C/±2.0°F	±1.0°C/±2.0°F
Temperature resolution	0.1°C/0.2°F	0.1°C/0.2°F
Humidity	0%RH~100%RH	0%RH~100%RH
Humidity accuracy	±5%RH	±5%RH
Humidity resolution	0.1%RH	0.1%RH
Sampling rate	1/s	1/s
<b>Features</b>		
APP		√
Bluetooth®		√
Overload indication	OL	OL
MAX/MIN	√	√
Data hold	√	√
°C/°F selection	√	√
LCD backlight	√	√
Auto power off	5 min	5 min
Low battery indication	3V~3.5V	3V~3.5V

UT333/UT333BT temperature humidity meters can measure, process data, and display results on LCD. UT333BT can transfer measurement data through bluetooth to UNI-T's custom mobile APP (iENV) for further analysis, storage, and export. iENV can be downloaded from Google Play, Apple Store or UNI-T's website by searching 'iENV'.

- Temperature measurement range: -10~60°C/14~140°F
- Humidity measurement range: 0~100%RH
- Light weight, ergonomic design, user-friendly interface
- MAX/MIN modes, low battery indication, auto power off

### GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 3
Display	32mm x 26mm
Product color	Red and grey
Product net weight	102g
Product size	155mm x 50mm x 28mm
Standard accessories	Batteries
Standard individual packing	Blister, English manual
Standard quantity per carton	<b>UT333:</b> 40pcs; <b>UT333 BT:</b> 20pcs
Standard carton measurement	<b>UT333:</b> 505mm x 330mm x 280mm <b>UT333 BT:</b> 332mm x 262mm x 290mm
Standard carton gross weight	<b>UT333:</b> 8kg; <b>UT333 BT:</b> 4.2kg