



BEAMZ
MADE
EAZY

150.640 150.641 V1.1

KUBE20

QUICK START GUIDE

CONTROL MENU

MENU				DESCRIPTION	
DMX ADDR	001-512			Address code settings	
CHANNEL	2CH			2 Channel Mode	
	6CH			6 Channel Mode	
	8CH			8 Channel Mode	
	11CH			11 Channel Mode	
DMX FAIL	Blackout			Console data black field	
	Hold			Console data retention	
FREQUENCY	600HZ			600 Refresh frequency	
	1200HZ			1200 Refresh frequency	
	2000HZ			2000 Refresh frequency	
	4000HZ			4000 Refresh frequency	
	12KHZ			12K Refresh frequency	
	25KHZ			25K Refresh frequency	
CUSTOM	Red:000-255			Red manual dimming	
	Green:000-255			Green manual dimming	
	Blue:000-255			Blue manual dimming	
	White:000-255			White manual dimming	
	Amber:000-255			Amber manual dimming	
	UV:000-255			Ultra Violet manual dimming	
PROGRAM	Static	Colour:01-32		32 static color blends	
		Speed:00-16		32 static color mixing strobe speeds (at a speed of 00, it is a static color mixing)	
	Auto	Speed:00-16		Color jump	
	Fade	Fade: 1	Speed:00-16		Color jump
		Fade: 2	Speed:00-16		
		Fade: 3	Speed:00-16		
	Sound	Sound:01	Sens:000-099		Voice controlled color change
		Sound:02	Sens:000-099		Voice controlled mutation
		Sound:03	Sens:000-099		Voice controlled color change strobe
		Sound:04	Sens:000-099		Voice controlled color change+ mutation+ color change strobe
	WiFi	LED_XXX		WiFi mode and link address	
	CCT	2000K	6000K		
		2200K	6400K		
		2400K	6800K		
		2600K	7200K		
		2800K	7600K		
		3200K	8000K		
3600K		8400K			
4000K		8800K			
4400K		9200K			
4800K		9600K			
5200K		10000K			
5600K					
MASTER/SLAVE	MASTER/SLAVE			Master/Slave	
WIRELESS DMX ON/OFF	0N	RD Protocol	ON/OFF	Paring	
				Clear	
		GZ Protocol			Group ID: 1,2,3,4,5,6,7
RUN TIME	2/4/6/8 hour			Lamp usage time setting	

BACK LIGHT	Always on	Display Normally Open Display Normally Open
	10s	Display standby for 10 seconds and turn off the screen
	20s	Display standby for 20 seconds and turn off the screen
	30s	Display standby for 30 seconds and turn off the screen
IR	ON/OFF	Infrared remote control on/off
MENU LOCK	ON/OFF	Key lock on/off (When locking the screen, press and hold the UP+DOWN key to unlock)
FACTORY RESET	NO/YES	System self check reset
CURVE	Led Curve 1	Linear curve
	Led Curve 2	Square curve
	Led Curve 3	Logarithmic curve
	Led Curve 4	S-curve
INFORMATION	Version V11	Software version

DMX CHANNELS

2 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	DIMMING	001-255	Total dimming
		000-010	Off light
		011-020	Color temperature 2000k
		021-030	Color temperature 2200K
		031-040	Color temperature 2400K
		041-050	Color temperature 2600K
		051-060	Color temperature 2800K
		061-070	Color temperature 3200K
		071-080	Color temperature 3600K
		081-090	Color temperature 4000K
		091-100	Color temperature 4400K
		101-110	Color temperature 4800K
		111-120	Color temperature 5200K
		2	COLOR TEMP.
131-140	Color temperature 6000K		
141-150	Color temperature 6400K		
151-160	Color temperature 6800K		
161-170	Color temperature 7200K		
171-180	Color temperature 7600K		
181-190	Color temperature 8000K		
191-200	Color temperature 8400K		
201-210	Color temperature 8800K		
211-220	Color temperature 9200K		
221-230	Color temperature 9600K		
231-240	Color temperature 10000K		
241-255	No function		

6 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	RED	001-255	Red linear dimming
2	GREEN	001-255	Green linear dimming
3	BLUE	001-255	Blue linear dimming
4	WHITE	001-255	White linear dimming
5	AMBER	001-255	Amber linear dimming
6	UV	001-255	Ultra Violet linear dimming

8 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	DIMMING	001-255	Total dimming
	OFF	000-009	Off light
2	STROBE	010-255	Strobe (slow to fast)
3	RED	001-255	Red linear dimming
4	GREEN	001-255	Green linear dimming
5	BLUE	001-255	Blue linear dimming
6	WHITE	001-255	White linear dimming
7	AMBER	001-255	Amber linear dimming
8	UV	001-255	Ultra Violet linear dimming

11 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	DIMMING	001-255	Total dimming
2	RED	001-255	Red linear dimming
3	GREEN	001-255	Green linear dimming
4	BLUE	001-255	Blue linear dimming
5	WHITE	001-255	White linear dimming
6	AMBER	001-255	Amber linear dimming
7	UV	001-255	Ultra Violet linear dimming
8	OFF	000-009	Off light
	STROBE	010-255	Strobe (slow to fast)
9	COLOR TEMP.	000-010	Off light
		011-020	Color temperature 2000K
		021-030	Color temperature 2200K
		031-040	Color temperature 2400K
		041-050	Color temperature 2600K
		051-060	Color temperature 2800K
		061-070	Color temperature 3200K
		071-080	Color temperature 3600K
		081-090	Color temperature 4000K
		091-100	Color temperature 4400K
		101-110	Color temperature 4800K
		111-120	Color temperature 5200K
		121-130	Color temperature 5600K
		131-140	Color temperature 6000K
		141-150	Color temperature 6400K
		151-160	Color temperature 6800K
		161-170	Color temperature 7200K
		171-180	Color temperature 7600K
		181-190	Color temperature 8000K
		191-200	Color temperature 8400K
		201-210	Color temperature 8800K
		211-220	Color temperature 9200K
		221-230	Color temperature 9600K
231-240	Color temperature 10000K		
241-255	No function		
10	MODE	000-009	Off light
		010-050	Static color mixing
		051-100	Jump mode
		101-150	Gradient mode
		151-200	Mutation pattern
		201-215	Color changing voice control
		216-230	Color strobe voice control
		231-245	Mutant voice control
		246-255	Breathing voice control
11	SPEED	001-255	Speed



A series of horizontal dotted lines spanning the width of the page, intended for handwriting practice.





A series of horizontal dotted lines for writing, spanning the width of the page.



BEAMZ

YOUR FUTURE
YOUR SKILLS
YOUR PLATFORM
YOUR PARTY
YOUR EVENT



offers a wide range of high performance lighting equipment and related accessories for the rental, entertainment and architectural lighting markets. BeamZ Pro stands for performance, innovation and value pricing!

