

CX-3008

SPEAKER CABINET

Order ref: 170.209

User Manual



Full range speaker enclosure made from premium Russian ply with custom drive units giving a wide bandwidth and smooth response for all styles of programme material.

Multiple flying points are fitted as standard for ease of installation and integration into arrays.


Computer-aided design for optimal tuning of enclosures delivering efficient output and bottom end response with strategic bracing to reduce resonance and improve projection.

- Durable textured black paint finish
- 12 x M10 flying points
- Powder-coated steel grille lined with dust filter
- Active electronic protection fitted to prevent overload to H.F. units
- Crossovers optimized for balanced integration of drivers
- Speakon® connectors fitted
- 35mm pole mount socket
- All fittings rebated for easier stacking and arraying
- Steel bar handles fitted as standard

Specifications


| | |
|----------------------------|--|
| Power RMS | 300W |
| Power Max | 500W (5 minutes max) |
| LF driver | 300mmØ (12") |
| HF driver | Compression driver with 44mmØ titanium diaphragm |
| Impedance | 8Ω |
| Frequency response (-3dB) | 60Hz - 18KHz |
| Frequency response (-10dB) | 50Hz - 20KHz |
| Sensitivity (1W/1m) | 97dB |
| Dispersion (H x V) | 90° x 40° |
| Connectors | 2 x Speakon® (NL 4) |
| Dimensions | 586 x 405 x 405mm |
| Weight | 27.5kg |

Technical drawings




Technical Diagrams


Frequency response - Magnitude




Impedance - Magnitude



Distortion - Magnitude



Combination - Magnitude



Connection

